


4-16MMØ BOLTS PER SPLICE



WHEEL GUARD SPLICE

- NOTES:
1. GALVANIZED WASHERS 75X75X8 PLACED ON BOTH ENDS OF ALL BOLTS.
 2. IF AADT > 2000VPD,
USE THRIE BEAM OR DOUBLE LAYER FLEXBEAM GUARDRAIL.
 3. IF AADT < 2000VPD,
SPLIT RINGS ARE NOT REQUIRED; CONNECTION TO ONE STRINGER ONLY

- IF DEPTH OF STRINGER IS \geq 450MM; IF CONNECTION TO ONE STRINGER ONLY, OUTSIDE STRINGER TO BE BLOCKED AND CONNECTED TO NEXT STRINGER AT A MAXIMUM 4.0M SPACING WITH 2-19MMØ BOLTS.
4. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE NOTED.

Manager Structural Engineering

 Director Highway Engineering Services

 Executive Director Highway Engineering and Construction

NOVA SCOTIA
 Transportation and Infrastructure Renewal

No.	REVISION

Scale : N.T.S.
 Drawn by : WRP
 Checked by : R.SWINEMAR
 Date of Plan : 2007-05-29
 File No. : B-2007-146

TIMBER BRIDGE BARRIER
PL1